



FLOOR CARE

Solutions

Ecolution® **FLOOR** **STRIPPER**



- Effectively and efficiently removes non-metallic floor finishes
- Low-odor formulation can be used while building is occupied
- Green Seal certified (GS-40; 2011)
- Designed for use with Ecolution® High Solids Floor Finish



stateindustrial.com

Care For Work Environments®



Ecolution® FLOOR STRIPPER

PRODUCT OVERVIEW :

SAFER FORMULA

Ecolution® Floor Stripper's heavy-duty formula is designed to remove Ecolution® High Solids Floor Finish and other non-metallic finishes. It does this without the harsh odors and fumes associated with conventional strippers.

EFFECTIVE STRIPPING

Ecolution® Floor Stripper utilizes superior penetrating and emulsifying properties to quickly break down the floor finish. Ecolution® Floor Stripper is not formulated with 2-butoxyethanol, yet it safely removes finish from all types of floors, including asphalt tile, asphalt planking, rubber, vinyl tile and terrazzo. It's easily rinsed, leaving a clean and residue-free surface. It has no harsh odors and is ideal where strong ammonia or solvent odors are a problem.

DIRECTIONS FOR USE :

1. Dust mop or sweep surface.
2. Remove any stickers, decals, etc. with a putty knife.
3. Add one gallon of Ecolution® Floor Stripper to five gallons of cold water.
4. Apply stripper generously to work area (200-400sq. ft./gal).
5. Let the solution stand for 5-10 minutes. If necessary, reapply stripper to areas that dry quickly.
6. Use a black pad on a 175 rpm floor machine to scrub floor.
7. Pickup solution with a wet vac or mop.
8. Rinse with clean, cool water until all residue is removed.

Dispose of unused product in accordance with Federal, State and Local regulations. Use product in accordance with prescribed use dilutions. Empty containers can be recycled.

Please review label and SDS on stateindustrial.com for all product directions, precautions and first aid information.

TECHNICAL DATA :

APPEARANCE: colorless to straw color liquid

ODOR: no fragrance

SPECIFIC GRAVITY: approximately 1.01

pH: 10.5 - 11.5

AMMONIA CONTENT: none

FINISH REMOVAL: best when used on non-metallic floor finishes

VOC CONTENT (DILUTED): complies with CARB limits



PACKAGING

115803	20 GL Drum
115802	5 GL Pail
119629	1 GL Bottle/GS4

CONTACT US

 stateindustrial.com

 support@stateindustrial.com

 1.866.747.2229

 5915 Landerbrook Drive, Mayfield Heights, OH 44124

