

# AIR CARE *Solutions*



**State**  
**FRESH  
ZONE™**  
**Odor Control Fogging System**



- Low flow high pressure system
- Corrosion resistant pump
- 30,000 hours of continuous operation
- Whisper quiet operation
- Easy installation and maintenance
- Recommended for outdoor usage

**state®**  
Since 1911

CARE FOR WORK ENVIRONMENTS®

# State FRESH ZONE™

## Odor Control Fogging System

State Fresh Zone Fogging system is compatible with all State Fresh Zone Products. It is just 4 different Fragrances: Fresh Zone Original, Fresh Zone Morning Fresh, Crisp Linen and Sweet Sunsatation.

The State Fresh Zone Fogging system uses a high pressure pump to develop the fog needed for effective and efficient odor neutralization. Each pump is enclosed in a lockable cabinet to prevent tampering. The pump is extremely durable, capable of continuous operation for more than 30,000 hours. Each pump is self priming and hydro tested before shipment. The fogging system is whisper quiet with less than 45 DBA and can run dry without damage (some priming may be required for dry pumps). The State Fresh Zone Fogging System can run intermittently with the use of a timer or continuously depending on the odor control needs. The wetted ends of the State Fresh Zone system are made with 3/8" easy to use Quick Connect fittings for easy assembly and disassembly.

**SFZ-6 Small Application:** For small outdoor spaces such as dumpsters, compactors and small loading areas use. Each SFZ-6 comes with:



- (1) Low flow high pressure pump
- (6) Fog nozzles and fittings
- (1) End plug
- Mounting hardware
- (1) Timer
- 50 Ft of tubing

**SFZ-20 Large Application:** For larger applications such as trash transfer stations, waste water lagoons, waste water clarifiers and loading docks. Each SFZ-20 comes with:



- (1) High flow high pressure pump
- (20) Fog nozzles and fittings
- 50 Ft of tubing
- (1) End plug
- Mounting hardware
- (1) Dilution tank for concentrated product. Proportioning control tips for concentrated product dilution

Applications: Each fogging nozzle uses approximately one gallon of fluid per hour of continuous operation

APPLICATION	RECOMMENDED NUMBER OF FOG NOZZLES
Trash Chutes or Compactors	2 per chute or compactor
Loading Docks and garage doors	1 nozzle per 3 ft perimeter
Lagoons, fields, and open areas	1 nozzle per 30 ft perimeter



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185

